

PORTABLE FIRE EXTINGUISHERS

Portable Fire Extinguishers are to be used to combat fire in its initial stages.

We offer a wide range of fire extinguishers to suit all types and classes of fire. **Combat**® Fire Extinguishers are made to rigorous standards of quality. They conform to the requirements of BS EN 3 and have achieved LPCB, SETSCO, PED (CE Mark), MED (Wheel Mark) and ISO 9001 certifications. All **Combat**® Fire Extinguishers are suitable for outdoor use – UV resistant.

According to SS 578 : 2012, the selection of suitable fire extinguishers depends on the fire hazards expected, occupancy of a building and the effectiveness of the fire extinguisher against that class of the hazard. Fire extinguishers shall be located in a conspicuous and readily accessible position and the travel distance to any fire extinguisher shall be 15m or less.



Dry Powder Stored Pressure Extinguisher

- BS EN 3 & SS EN 3
- Effective on Class A and B fires
- Does not conduct electricity
- Fast knock out effect
- Environmentally friendly fire extinguisher for ABC powder type
- Widely used in residential & commercial buildings, industrial plants and workshops etc.



Capacity	1kg	2kg	3kg	4kg	6kg	9kg	12kg	9kg	9kg
Extinguishing Medium	ABC 40% Dry Chemical Powder							Monnex	Purple K
Propellant Gas	Nitrogen								
Fire Rating	5A/55B/C	13A/55B/C	13A/55B/C	21A/144B/C	34A/233B/C	43A/233B/C	55A/233B/C	233B	233B
Design Pressure	14 bar								
Design Temperature	-20°C to 60°C								
Hose Length	N.A.		440mm	440mm	530mm	620mm	530mm	530mm	530mm
Size (D*H) mm	85 x 320	98 x 455	115 x 470	139 x 465	181 x 510	181 x 606	181 x 634	181 x 606	181 x 606



Foam Stored Pressure Extinguisher

- BS EN 3 & SS EN 3
- Effective on Class A and B fires
- Environmentally friendly fire extinguisher
- To replace ABC fire extinguisher for general usage. (No residual mess)
- Not applicable for fire involving electrical equipment
- Widely used in shopping malls, schools, offices, industrial factories, storage areas, paint shops and petrol stations.



Capacity	6ltr	9ltr
Extinguishing Medium	SC-1 Foam	
Propellant Gas	Nitrogen	
Fire Rating	8A/113B	34A/233B
Design Pressure	14 bar	
Design Temperature	5°C to 60°C	
Hose Length	295mm	530mm
Size (D*H) mm	181 x 510	181 x 605



Water Stored Pressure Extinguisher

- BS EN 3 & SS EN 3
- Not applicable for fire involving electrical equipment
- Widely used in retail shops, printing firms and wood industries
- Effective on Class A fires



Capacity	6ltr	9ltr
Extinguishing Medium	Water	
Propellant Gas	Nitrogen	
Fire Rating	8A	13A
Design Pressure	14 bar	
Design Temperature	5°C to 60°C	
Hose Length	295mm	530mm
Size (D*H) mm	181 x 510	181 x 605



Carbon Dioxide Stored Pressure Extinguisher

- BS EN 3 & SS EN 3
- Heavy duty hose & high-pressure hardware
- Suitable for use on live electrical equipment
- Effective suppression of Class B fires



Capacity	2kg	5kg
Extinguishing Medium	CO2	
Propellant Gas	CO2	
Fire Rating	34B/C	55B/C
Design Pressure	60 bar	
Design Temperature	-20°C to 60°C	
Hose Length	295mm	440mm
Size (D*H) mm	114 x 492	165 x 655



Halotron™ I Stored Pressure Extinguisher

- SS232
- Eco-friendly replacement for Halon 1211
- Clean gas with no residue and safe for the environment
- High performance and lightweight
- Effective on Class A, B, C & E fires
- Widely used in offices, M&E rooms and server rooms



Capacity	2kg	4kg	6kg
Extinguishing Medium	Halotron I		
Propellant Gas	Argon		
Fire Rating	5A/34 B/C	8A/55 B/C	13A/70 B/C
Design Pressure	6.9 bar	8.63 bar	
Design Temperature	-20°C to 60°C		
Hose Length	440mm		
Size (D*H) mm	98 x 455	139 x 460	181 x 505



Wet Chemical Stored Pressure Extinguisher

- BS EN 3 & SS EN 3
- Latest requirement by SCDF to install next to deep fryers
- Hose applicator and nozzle
- Effective for kitchen fire
- Effective on Class A, B & F fires



Capacity	6ltr
Extinguishing Medium	Fatseal
Propellant Gas	Nitrogen
Fire Rating	21A
Design Pressure	14 bar
Design Temperature	0°C to 60°C
Hose Length	490mm
Size (D*H) mm	160 x 514